

HM

HRC


04220

Frese per stampi

Visit the online
Product Sheet

F04220H00150074

2 flute ball nose end mill for ribbing with tapered neck and reinforced shank

Silmax
NORM $\lambda 30^\circ$ 

Details

Diameter of cutting edge D +0/-0,02	1,50
Corner Radius/Radius Cr/r	0,75
Cutting length l	1,35
Neck Relief Length l1	10,0
Neck diameter d1	1,45
Tapered neck length l2	20,0
Neck Angle α	1,9
Engaged Angle β	12,0
Overall Length L	78
Shank Diameter d h5	6,00
$\varepsilon 0,5^\circ$	
$\varepsilon 0,5^\circ$	14,32
$\varepsilon 1,0^\circ$	
$\varepsilon 1,0^\circ$	20,15
$\varepsilon 2,0^\circ$	
$\varepsilon 2,0^\circ$	22,05
$\varepsilon 3,0^\circ$	
$\varepsilon 3,0^\circ$	24,38

Materials

Steel < 800 n/mm ²	
Steel < 1000 n/mm ²	
Steel < 1300 n/mm ²	
Hardened steel 42 ÷ 52 HRC	
Hardened steel 52 to 62 HRC	

Coatings

Balinit® Tisaflex (HMH)

Alternative Coatings

Series normal



Number of Flutes

Z	2
---	---

Shank references standard

Rif. gambo	HA
------------	----

This tool is available in 6 diameters.

 Please consider the environment, before printing this document.