



Visit the online  
Product Sheet

# HMC4058A034


5xD Drilling-Boring with internal coolant



Silmax  
NORM

DIN  
6535 HA  
(Standard)

$\lambda$  30°



## Details

|                                   |       |
|-----------------------------------|-------|
| Diameter of cutting edge<br>d1 m7 | 3,40  |
| Shank Diameter<br>d2 h6           | 6,00  |
| Cutting length<br>lu              | 23,00 |
| Flute length<br>l2                | 28,0  |
| Shank length<br>l4                | 36,0  |
| Overall Length<br>l1              | 66    |

## Materials

|                                |                        |
|--------------------------------|------------------------|
| Steel < 800 n/mm <sup>2</sup>  | <div><div></div></div> |
| Steel < 1000 n/mm <sup>2</sup> | <div><div></div></div> |
| Steel < 1300 n/mm <sup>2</sup> | <div><div></div></div> |
| Ferritic/Martensitic steel     | <div><div></div></div> |
| Austenitic steel               | <div><div></div></div> |
| PH Duplex                      | <div><div></div></div> |
| Grey cast iron                 | <div><div></div></div> |

## Coatings

Balinit® Latuma (HMC)

## Alternative Coatings

This tool is available in 105 diameters.

 Please consider the environment, before printing this document.