



Visit the online  
Product Sheet

# HMC4058A190


5xD Drilling-Boring with internal coolant



Silmax  
NORM

DIN  
6535 HA  
(Standard)

$\lambda$  30°



## Details

|                          |       |
|--------------------------|-------|
| Diameter of cutting edge |       |
| d1 m7                    | 19,00 |
| Shank Diameter           |       |
| d2 h6                    | 20,00 |
| Cutting length           |       |
| lu                       | 75,00 |
| Flute length             |       |
| l2                       | 99,0  |
| Shank length             |       |
| l4                       | 50,0  |
| Overall Length           |       |
| l1                       | 151   |

## Materials

|                                |                        |
|--------------------------------|------------------------|
| Steel < 800 n/mm <sup>2</sup>  | <div><div></div></div> |
| Steel < 1000 n/mm <sup>2</sup> | <div><div></div></div> |
| Steel < 1300 n/mm <sup>2</sup> | <div><div></div></div> |
| Ferritic/Martensitic steel     | <div><div></div></div> |
| Austenitic steel               | <div><div></div></div> |
| PH Duplex                      | <div><div></div></div> |
| Grey cast iron                 | <div><div></div></div> |

## Coatings

Balinit® Latuma (HMC)

## Alternative Coatings

This tool is available in 105 diameters.

 Please consider the environment, before printing this document.